	CONFIDENTIAL		
	CLASSIFICATION BECREE  CENTRAL INTELLIGENCE AGENCY	REPOR	
	INFORMATION REPORT	CD NO.	50X1-HUI
COUNTRY	Germany (Russian Zone)	DATE DISTR.	22 January 1951
SUBJECT	Quality of Fuel Oil Produced by the Teerverarbeitungswerk Webau	NO. OF PAGES	1
PLACE ACQUIRED		NO. OF ENCLS.	50X1-HU
DATE OF INFO.		SUPPLEMENT REPORT NO.	
			50X1-HUN
	the fuel oil produced consists mainly or creosotes. These creosotes are oil, extracted from raw materials from the lignite a process utilizing a caustic soda solution. and "	of two kinds: (carbonization pi	creosote Lant by
	consists mainly of cressotes. These cressotes are	of two kinds: carbonization pi fresol, obtained tar. Webau's fue e) and residues I This fuel oil, b t, congeals at a lower calorific t 4 to 7 degrees h s. As the technic ng better fuel oil of the fuel oil	areosote lant by i by el oil left ecause tem- value agler eal li,
	consists mainly or creosotes. These creosotes are oil, extracted from raw materials from the lignite a process utilizing a caustic soda solution, and "extracting alcohol from the carbonization plant's also contains so-called red products (Rote Produkt after the distillation of medium and heavy oils. of its high asphalt, paraffin, and creosote contemperature considerably above that prescribed. The registered at 8,600 to 9,000 and the viscosity of at 20°C are, for the same reason below requirement; facilities of the plant are inadequate for product it is suggested that the Webau plant process part impregnating oil and that the remainder be shipped	of two kinds: carbonization pi fresol, obtained tar. Webau's fue e) and residues I This fuel oil, b t, congeals at a lower calorific t 4 to 7 degrees h s. As the technic ng better fuel oil of the fuel oil	areosote lant by i by el oil left ecause tem- value agler eal li,
	consists mainly or creosotes. These creosotes are oil, extracted from raw materials from the lignite a process utilizing a caustic soda solution, and "extracting alcohol from the carbonization plant's also contains so-called red products (Rote Produkt after the distillation of medium and heavy oils. of its high asphalt, paraffin, and creosote contemperature considerably above that prescribed. The registered at 8,600 to 9,000 and the viscosity of at 20°C are, for the same reason below requirement; facilities of the plant are inadequate for product it is suggested that the Webau plant process part impregnating oil and that the remainder be shipped	of two kinds: carbonization pi fresol, obtained tar. Webau's fue e) and residues I This fuel oil, b t, congeals at a lower calorific t 4 to 7 degrees h s. As the technic ng better fuel oil of the fuel oil	areosote lant by i by el oil left ecause tem- value agler eal li,
	consists mainly or creosotes. These creosotes are oil, extracted from raw materials from the lignite a process utilizing a caustic soda solution, and "extracting alcohol from the carbonization plant's also contains so-called red products (Rote Produkt after the distillation of medium and heavy oils. of its high asphalt, paraffin, and creosote contemperature considerably above that prescribed. The registered at 8,600 to 9,000 and the viscosity of at 20°C are, for the same reason below requirement; facilities of the plant are inadequate for product it is suggested that the Webau plant process part impregnating oil and that the remainder be shipped	of two kinds: carbonization pi fresol, obtained tar. Webau's fue e) and residues I This fuel oil, b t, congeals at a lower calorific t 4 to 7 degrees h s. As the technic ng better fuel oil of the fuel oil	areosote lant by i by el oil left ecause tem- value agler eal li,
	consists mainly or creosotes. These creosotes are oil, extracted from raw materials from the lignite a process utilizing a caustic soda solution, and "extracting alcohol from the carbonization plant's also contains so-called red products (Rote Produkt after the distillation of medium and heavy oils. of its high asphalt, paraffin, and creosote contemperature considerably above that prescribed. The registered at 8,600 to 9,000 and the viscosity of at 20°C are, for the same reason below requirement; facilities of the plant are inadequate for product it is suggested that the Webau plant process part impregnating oil and that the remainder be shipped	of two kinds: carbonization pi fresol, obtained tar. Webau's fue e) and residues I This fuel oil, b t, congeals at a lower calorific t 4 to 7 degrees h s. As the technic ng better fuel oil of the fuel oil	areosote lant by i by el oil left ecause tem- velue ngler cel li, into
	consists mainly or creosotes. These creosotes are oil, extracted from raw materials from the lignite a process utilizing a caustic soda solution, and "extracting alcohol from the carbonization plant's also contains so-called red products (Rote Produkt after the distillation of medium and heavy oils. of its high asphalt, paraffin, and creosote contemperature considerably above that prescribed. The registered at 8,600 to 9,000 and the viscosity of at 20°C are, for the same reason below requirement; facilities of the plant are inadequate for product it is suggested that the Webau plant process part impregnating oil and that the remainder be shipped	of two kinds: carbonization pi fresol, obtained tar. Webau's fue e) and residues I This fuel oil, b t, congeals at a lower calorific t 4 to 7 degrees h s. As the technic ng better fuel oil of the fuel oil	areosote lant by i by el oil left ecause tem- value agler eal li,
	consists mainly of cressotes. These cressotes are oil, extracted from raw materials from the lignite a process utilizing a caustic soda solution, and materiating alcohol from the carbonization plant's also contains so-called red products (Rote Produkt after the distillation of medium and heavy oils. of its high asphalt, paraffin, and creosote contemperature considerably above that prescribed. The registered at 8,600 to 9,000 and the viscosity of at 20°C are, for the same reason below requirements facilities of the plant are inadequate for product it is suggested that the Webau plant process part impregnating oil and that the remainder be shipped for hydrogenation.	of two kinds: carbonization pi fresol, obtained tar. Webau's fue e) and residues I This fuel oil, b t, congeals at a lower calorific t 4 to 7 degrees h s. As the technic ng better fuel oil to the Leuna pla	areosote lant by i by el oil left ecause tem- velue ngler cel ll; into
	consists mainly of creosotes. These creosotes are oil, extracted from raw materials from the lignite a process utilizing a caustic soda solution, and extracting alcohol from the carbonization plant's also contains so-called red products (Rote Produkt after the distillation of medium and heavy oils. of its high taphalt, paraffin, and creosote contemperature considerably above that prescribed. The registered at 8,600 to 9,000 and the viscosity of at 20°C are, for the same reason below requirements facilities of the plant are inadequate for product it is suggested that the Webau plant process part impregnating oil and that the remainder be shipped for hydrogenation.	of two kinds: carbonization pi fresol, obtained tar. Webau's fue e) and residues I This fuel oil, b t, congeals at a lower calorific t 4 to 7 degrees h s. As the technic ng better fuel oil to the Leuna pla	areosote lant by i by el oil left ecause tem- velue ngler cel li, into

.